



BELLE  
LIGHT  
CONSTRUCTION  
EQUIPMENT



Altrad-Belle.com

# BHB RANGE

## HYDRAULIC BREAKERS



Sturdy and reliable hydraulic breakers designed for working together with Altrad Belle Hydraulic Power Packs.

The handheld breakers are available in many different sizes with varying impact energies and commonly used tool sizes.



BUILDING A SUSTAINABLE FUTURE

## FEATURES & BENEFITS

- Improved, lock-on, ergonomic handgrips.
- Compatible with the range of Altrad Belle Hydraulic Power Packs.
- Frequency and Blow Rates to achieve maximum productivity.
- For use on a number of materials, from light brickwork to asphalt.
- Delivered with 1/2" tail-hoses with 1/2" at-face couplings.
- Hoses are removable for easy transportation and storage. Can also be changed quickly if damaged.
- Very reliable and simple to maintain = less servicing costs.



**IMPROVED, LOCK-ON, ERGONOMIC HANDGRIPS**



**RANGE OF STEELS AVAILABLE INC. A RAMMER STEEL OPTION**

## TECHNICAL SPECIFICATIONS

Model	BHB 12 (BHB12S)
Max Pressure	(bar) 160
Hydraulic Flowrate	(l/min) 20
Blows per Minute	2400
3-Axis Vibration	(m/sec <sup>2</sup> ) **16.08
Breaking Force	(J) 25
Steel Size	(mm) 22 x 82
Weight	(kg) 14
Sound Power Level	(dB L <sub>WA</sub> ) 105

Model	BHB 23 (BHB23S)
Max Pressure	(bar) 160
Hydraulic Flowrate	(l/min) 20
Blows per Minute	1600
3-Axis Vibration	(m/sec <sup>2</sup> ) **11.97
Breaking Force	(J) 65
Steel Size	(mm) 25 x 108
Weight	(kg) 23.5
Sound Power Level	(dB L <sub>WA</sub> ) 107

Model	BHB 25 (BHB25S)
Max Pressure	(bar) 160
Hydraulic Flowrate	(l/min) 20
Blows per Minute	1300
3-Axis Vibration	(m/sec <sup>2</sup> ) **11.1
Breaking Force	(J) 85
Steel Size	(mm) 32 x 160
Weight	(kg) 28
Sound Power Level	(dB L <sub>WA</sub> ) 108

Model	BHB 25X (BHB25XS)
Max Pressure	(bar) 160
Hydraulic Flowrate	(l/min) 20
Blows per Minute	1600
3-Axis Vibration	(m/sec <sup>2</sup> ) **6.5
Breaking Force	(J) 55
Steel Size	(mm) 32 x 160
Weight	(kg) 25
Sound Power Level	(dB L <sub>WA</sub> ) 108

Model	BHB 27 (BHB27S)
Max Pressure	(bar) 160
Hydraulic Flowrate	(l/min) *20/30
Blows per Minute	1300 (20ltr)
Blows per Minute	2150 (30ltr)
3-Axis Vibration	(m/sec <sup>2</sup> ) **11.8 (20ltr)
3-Axis Vibration	(m/sec <sup>2</sup> ) **18.6 (30ltr)
Breaking Force	(J) 85
Steel Size	(mm) 32 x 160
Weight	(kg) 27
Sound Power Level	(dB L <sub>WA</sub> ) 108

Model	BHB 27X (BHB27XS)
Max Pressure	(bar) 160
Hydraulic Flowrate	(l/min) *20/30
Blows per Minute	1300 (20ltr)
Blows per Minute	2150 (30ltr)
3-Axis Vibration	(m/sec <sup>2</sup> ) **8.2 (20ltr)
3-Axis Vibration	(m/sec <sup>2</sup> ) **6.8 (30ltr)
Breaking Force	(J) 85
Steel Size	(mm) 32 x 160
Weight	(kg) 30
Sound Power Level	(dB L <sub>WA</sub> ) 108

\* NOTE:- Breaker is supplied with alternative return pipe restrictors. Please ensure correct restrictor is fitted for 20 (3.4mm Restrictor) or 30 (Open Restrictor) Litre supply. (Restrictor size is marked on the restrictor body)  
**NO MARKINGS = OPEN RESTRICTOR**

\*\* OPERC Independent testing Vibration levels tested to BS28927-10

ALTRAD BELLE RESERVES THE RIGHT TO AMEND OR IMPROVE ANY SPECIFICATIONS IN THIS BROCHURE WITHOUT NOTICE.

