



BELLE  
LIGHT  
CONSTRUCTION  
EQUIPMENT



Altrad-Belle.com

# TDX 650

## TWIN-DRUM ROLLER

A twin-drum walk-behind roller with hydrostatic drive system.

The TDX 650 has a high compaction force with well positioned controls making it easy to operate.

Suitable for a wide range of sub-base and asphalt compaction applications.



BUILDING A SUSTAINABLE FUTURE.

## FEATURES & BENEFITS

- Highly responsive, low-maintenance Hydrostatic drive system.
- High-powered, reliable, 10hp Air-Cooled, Electric Start Yanmar Diesel engine. Recoil Start back-up.
- 20kN high compaction force for productivity
- Enclosed engine compartment with lockable canopy for secure, easy access.
- High-quality Hydraulic System components.
- 65 litre Water Tank with external gauge.
- Wall clearance on both sides with no overhang.
- Self-cleaning, adjustable Scraper Bars.
- 18 litre Hydraulic Oil Tank.
- Easy access, removable, front and rear anticorrosive water sprinkler system.
- Foldable handle with locking mechanism.
- Lockable Diesel fill access flap.
- Easy to service - Remote Oil Drain.
  - Remote Oil Fill.
  - Air Cleaner Access.
- Drain on Water Tank to prevent frost damage.
- Centrally located Lifting Eye and 4 Strapping/ Lifting Points.
- Key Switch protection.
- Ignition Warning System.
- Customer colour options available.
- Optional Hourmeter available.



**WELL POSITIONED, EASY TO OPERATE CONTROLS**



**PRE-CLEANER AS STANDARD**



**ABILITY TO BE USED RIGHT UP TO KERB EDGES**

## TECHNICAL SPECIFICATIONS

<b>Model</b>	<b>TDX 650</b>	
Part No.	TDX650GRY4	
Width	(mm)	702
Drum Width	(mm)	650
Length	(mm)	2272
Height	(mm)	1093
Engine Type	Yanmar L100N	
Engine Power	(Hp / kW)	9.2 / 6.8
Fuel Type	Diesel	
Starting System	Electric	
Water Tank Capacity	(Ltr)	65
Oil Tank Capacity	(Ltr)	18
Forward Speed	(km/hr)	> 3.9
Reverse Speed	(km/hr)	> 2.1
Centrifugal Force	(kN)	20
Vibration Frequency	(vpm)	3300
Weight	(kg)	775
Sound Power Level	(dB LWA)	107

ALTRAD BELLE RESERVES THE RIGHT TO AMEND OR IMPROVE ANY SPECIFICATIONS IN THIS BROCHURE WITHOUT NOTICE.

