









BGA FLEXIBLE SHAFT PUMPS





FEATURES & BENEFITS

- A heavy duty and durable pump designed to work in tough site conditions.
- Capable of pumping dirty water even when containing small solids.
- Provides the ability to lift high heads of water at excellent flow rates.
- Works off standard poker drive units for maximum versatility.



'TWO DOG' DRIVE COUPLING



FIREMAN'S COUPLING 3"

TECHNICAL SPECIFICATIONS

Model	BGA 5M Pump		Model	Honda Petrol Unit	
Part No.	165.9.047	•	Engine power	(Hp / kW)	4/3
Maximum Flow rate	(litre/h)	25000	Engine speed	(rpm)	2800
Speed Ratings	(rpm)	2800-3600	Width	(mm)	420
Shaft Length	(m)	5	Height	(mm)	520
Outlet Size	(mm)	75	Length	(mm)	445
Pump Weight	(kg)	6	Weight	(kg)	24
Total Weight	(kg)	19.5			

Model

Part No.
Maximum Flow rate
Speed Ratings
Shaft Length
Outlet Size
Pump Weight
Total Weight

Options

165.0.169 165.0.170 OPB/02/DIO

BGA 7M Pump

BGAP02
(litre/h) 25000
(rpm) 2800-3600
(m) 7
(mm) 75
(kg) 10
(kg) 28

3" Lay Flat House 2 No 3" Circlip For Hose Fireman's Coupling 3"

Model

Engine power Engine speed Width Height Length Weight

Model

Engine power Engine speed Width Height Length Weight

Hatz Diesel Unit

(Hp / kW) 5.4 / 4 (rpm) 2800 (mm) 430 (mm) 630 (mm) 500 (kg) 43

Yanmar Diesel Unit

(Hp / kW) 4.2 / 3.1 (rpm) 2800 (mm) 430 (mm) 630 (mm) 500 (kg) 38



ALTRAD BELLE

Sheen, Nr. Buxton, Derbyshire, SK17 OEU, GB Tel. +44 (0)1298 84606 - Fax +44 (0)1298 84722 - Email: sales@altrad-belle.com

www.Altrad-Belle.com www.ALTRAD-Belle247.com

