



## **EASY SCREED PRO**

## FREE SCREEDER

A high performance free screeding machine, ultimately designed for levelling and vibrating concrete slabs without the need to run off supporting form work.

The drive unit provides control and high power vibration to a reinforced aluminium beam.

The tool free removal and reversing of the uniquely shaped beam also allows striking off across traditional form work.



## **FEATURES & BENEFITS**

- Adjustable centrifugal force from the vibrator unit optimises performance with different concrete slumps and beam lengths. This ensures effective compaction and finishing.
- In-line flex. drive shaft for durability & reliability.
- High power 4-stroke Honda engine for high performance and reliability.
- Height adj. handles for operator comfort & control.
- Isolators ensure vibration is transmitted to the concrete and not the operator.
- Tool-free Quick Clamp enables quick & easy removal of the beam for transport & storage.
- Double-sided beam profile with one side designed for form free screeding and the other for striking off between form work.
- Heavily reinforced beam for ultimate strength and vibration transmission.
- Different beam lengths available from 1.5m to 6m.



IN-LINE FLEXIBLE DRIVE SHAFT



ADJUSTABLE CENTRIFUGAL FORCE

## **TECHNICAL SPECIFICATIONS**

| Model                     | Easy Screed Pro       |                   | Model                        | 3.0m Beam (157.3.003)  |                      |
|---------------------------|-----------------------|-------------------|------------------------------|------------------------|----------------------|
| Part No.                  |                       | 157.9.010         | Dimensions (WxLxH)           | (mm)                   | 200x100x3000         |
| Engine Power              | (Hp/kW)               | 1.3 / 1.0         | Weight                       | (kg)                   | 12.5                 |
| Frequency                 | (Hz)                  | 83                | Model                        | 3.75m Beam (157.3.004) |                      |
| Compaction Depth          | (mm)                  | 75                | Dimensions (WxLxH)           | (mm)                   | 200x100x3750         |
| Dimensions (WxLxH)        | (mm)                  | 630x440x1040      | Weight                       | (kg)                   | 15.5                 |
| Weight                    | (kg)                  | 16                | Model                        | 4.25m Beam (157.3.005) |                      |
|                           |                       |                   | Dimensions (WxLxH)           | (mm)                   | 200x100x4250         |
|                           |                       |                   | Weight                       | (kg)                   | 17.5                 |
| Model                     | 1.5m Beam (157.3.000) |                   | Model                        | 5.0m Beam (157.3.006)  |                      |
| Dimensions (WxLxH)        | (mm)                  | 200x100x1500      | Dimensions (WxLxH)           | (mm)                   | 200x100x5000         |
| Weight                    | (kg)                  | 6                 | Weight                       | (kg)                   | 20.5                 |
| Model                     | 1.9m Beam (157.3.001) |                   | Model                        | 5.5m Beam (157.3.007)  |                      |
|                           |                       |                   |                              |                        | (                    |
| Dimensions (WxLxH)        | (mm)                  | 200x100x1900      | Dimensions (WxLxH)           | (mm)                   | 200x100x5500         |
| Dimensions (WxLxH) Weight | (mm)<br>(kg)          | 200x100x1900<br>8 | Dimensions (WxLxH)<br>Weight |                        |                      |
| ,                         | (kg)                  |                   | ,                            | (mm)<br>(kg)           | 200x100x5500         |
| Weight                    | (kg)                  | 8                 | Weight                       | (mm)<br>(kg)           | 200x100x5500<br>22.5 |



