

ASP 6 L-2

The basic model of the vertical log splitters for simple firewood-preparation

natural and cost-efficient heating with firewood

2-hand operation with handle guards
chassis and transport handle for an easy manoevrability

according to the latest European standard





The basic model of the vertical log splitters is perfect, to process logs to firewood comfortably, quickly, safely and effortlessly.

The ideal solution for the privat user, the owner of wood-burning stoves and tiled stoves.

- Equipped with a powerful motor which ensure good splitting results.
- The sturdy construction guarantees a high stability.
- According to the latest safety requirements to the European standards. Increased operational safety due to
 - the smooth 2-hand safety operation with handle guards.
 - the tipping protection that prevents the split wood from falling down uncontrollably.
 - the trays for the splitted logs.
- The chassis and the transport handle guarantee a fast and easy manoeuvrability.



Log splitter

Order number	301730
Motor	230 V ~ 50 Hz
Input power P ₁ (S6 4 min/6 min)	3000 W (S6 - 40%)
Splitting force	60 kN (6 t) ±10%
Log length max.	495 mm
Stroke max.	100 - 550 mm
Diameter of log max.	80 - 300 mm
Length of splitting wedge	175 mm
Splitting pillar	85 x 85 mm
System pressure	21.6 Mpa
Hydraulic oil capacity	3.5 L
Speed (forward / retract)	3.6 cm/s / 16.5 cm/s
Sound pressure L _{PA} (no load operation / on operation)	78.5 dB (A) / 89.8 dB (A)
2-hand operation with handle guards	✓
Chassis and transport handle	✓
Weight approx.	98.5 kg

ASP 6 L-2

Technical modifications reserved.