



## **PORTO SCREED**

## TWIN-BEAM SCREED



## **FEATURES & BENEFITS**

- Drive unit is plated for easy cleaning and to prevent corrosion.
- Concrete is vibrated to a depth of 150mm.
- Enclosed vibrator and drive housing for lower maintenance.
- Fitted with low Hand-Arm Vibration comfort handles for easy pulling.
- Quick Clamp system for tool free on site assembly.
- Drive unit under 50kg for an easy two-man lift on site.
- Simplicity, ease of use and robustness, suits rental organisations.
- A range of fixed and extending beams available from 3.25m to 7.2m lengths.



LOW HAND-ARM VIBRATION COMFORT HANDLES



CAPABLE OF SCREEDING AREAS UP TO 7.2 METERS



'QUICK CLAMP' SYSTEM FOR TOOL FREE ON SITE ASSEMBLEY

## **TECHNICAL SPECIFICATIONS**

Model		Porto Screed
Part No.		149.9.000
Engine Type		Honda
Engine Power	(Hp / Kw)	3.3 / 2.4
Frequency	(Hz)	80
Compaction Depth	(mm)	150
Force	(kN)	3.1
Sound Power Level	(dB L <sub>WA</sub> )	104
Vibration Level	(m/sec²)	5.88
Width	(mm)	704
Height	(mm)	440
Length	(mm)	1040
Weight	(kg)	49

Part No.	Description
36.8.031	5.2m Beam
36.8.032	6.2m Beam
36.8.033	7.2m Beam
149.3.004	Extending Bear

149.3.004 Extending Beam (3.25-5.2m)

149.3.003 End Frames x 2

149.3.001 Solid End Pull Handles x 2



