



BELLE  
LIGHT  
CONSTRUCTION  
EQUIPMENT



Altrad-Belle.com

# DUO 350X

## TWIN-BLADE FLOOR SAW

A robust, high standard Twin Blade Floor Saw specifically designed for Micro-Trenching.

Designed with the industry's lowest Hand Arm Vibration levels. Features an engine protection frame to protect the saw in the worst of conditions.

Simple to operate and safe to use and can be used for single blade operation also. **The ideal contractors' saw.**



BUILDING A SUSTAINABLE FUTURE.

## FEATURES & BENEFITS

- Low Hand Arm Vibration levels - Patented design.
- Twin Blade setup reduces operation times.
- Innovative Guard that never exposes the Blades.
- 100mm cutting width, ideal for trench cutting.
- Easily transported (Fits into back of small van)
- Specially moulded 25 litre detachable water tank with in-built water level gauge.
- Foot operated depth adjustment for speed, simplicity and safety.
- Robust construction to survive the heaviest contract work.
- Can be used with a single Blade.



**VIBRATION DAMPING COMFORT HANDLE**



**REMOVABLE WATER TANK WITH IN-BUILT WATER LEVEL GAUGE**



**TWIN BLADE SETUP REDUCES OPERATION TIME**



**100MM CUTTING WIDTH**

## TECHNICAL SPECIFICATIONS

<b>Model</b>	<b>Duo 350X</b>	
Part No.		DSXA01
Engine Power	(Hp / kW)	11.8 / 8.7
Engine Model		Honda GX390
Engine Type		Petrol
Blade Speed	(rpm)	3600
Max. Cutting Depth	(mm)	120
Cutting Width	(mm)	100
Blade Diameter	(mm)	350
Water Tank Capacity	(ltr)	25
Width	(mm)	618
Height	(mm)	1019
Length	(mm)	870
Weight	(kg)	120
3 Axis Vibration	(m/sec <sup>2</sup> )	3.67
Usage Time	(mins)	223
Noise Level	(dB(A))	114

ALTRAD BELLE RESERVES THE RIGHT TO AMEND OR IMPROVE ANY SPECIFICATIONS IN THIS BROCHURE WITHOUT NOTICE.

