



BGA RANGE

SUBMERSIBLE WATER PUMPS

High capacity flexible shaft submersible pump with an output of 72m³/hour.

For draining and removal of water from trenches and building sites without the use of electric power.





FEATURES & BENEFITS

- A heavy duty and durable pump designed to work in tough site conditions.
- Capable of pumping dirty water even when containing small solids up to 15mm in diameter.
- High output and a flow rate of 72 m³/h.
- Provides the ability to lift high heads of water at excellent
- Simple to use; priming not necessary.
- Durable cast steel impellar.
- Strong, 5 metre flexible shaft.
- Two-dog coupling identical to Altrad Belle BGA Pokers which enables compatibility and versatility in utilisation between water removal and concreting work.
- Works off standard poker drive units for maximum versatility.
- Honda & Loncin Petrol or Hatz Diesel power unit options available.



'TWO DOG' DRIVE COUPLING



3" FIREMAN'S COUPLING OPTION

TECHNICAL SPECIFICATIONS

Model	BGA 5M Pump		Model	Honda GX160 Power Unit	
Part No.		165.9.047	Part No.		165.9.038
Maximum Flow Rate	(m ³ /h)	72	Engine power	(Hp/kW)	4.9 / 3.6
Speed Ratings	(rpm)	2800-3600	Engine speed	(rpm)	2800
Shaft Length	(m)	5	Width	(mm)	420
Outlet Size	(mm)	75	Height	(mm)	520
Pump Weight	(kg)	6	Length	(mm)	445
Pump & Shaft Weight	(kg)	22	Weight	(kg)	26

Options

165.0.169	3" Lay Flat House
165.0.170	3" Circlip For Hose x 2
OPB/02/DIO	3" Fireman's Coupling

Model

Part No.
Engine power
Engine speed
Width
Height
Length
Weight

Model

model
Part No.
Engine powe
Engine speed
Width
Height
Length
Weight

	100.7.000
(Hp/kW)	4.9 / 3.6
(rpm)	2800
(mm)	420
(mm)	520
(mm)	445
(kg)	26

Loncin H135 Power Unit

	165.9.090
(Hp/kW	3.5 / 2.6
(rpm)	2800
(mm)	420
(mm)	520
(mm)	445
(kg)	24

Hatz 1B20 Power Unit

	165.9.034
(Hp/kW)	4.6 / 3.4
(rpm)	2800
(mm)	420
(mm)	630
(mm)	500
(kg)	43



